

RECOMMENDED USES



HIT 250 WR HDRY

219442 AG1

STANDARD	SIZE
S3 SRC WR	38/48
COLOURS	WEIGHT
Asphalt All Black Radiant Yellow	570 gr
ELECTRIC CATEGORY	FIT
Antistatic	11

COMPONENTS

- Upper:** Special HDRY membrane, waterproof and breathable sealed directly to the upper thanks to the innovative 3D lamination process.
- Upper lining:** Breathable mesh fabric with durable microfiber heel abrasion.
- Toe-cap:**
 - Aluminium toe-cap with large internal space for improved toe comfort.
 - 200 Joule impact protection.
 - Compression protection 1,500 kg.
- Anti-intrusion insole:** Made of anti-perforation, absorbent, abrasion- and flaking-resistant fabric.
- Sole:** Made of antistatic bidensity polyurethane, directly injected onto the upper with electrostatic charge dissipation capacity.
- Tread:** High density, non-slip (SRC), abrasion- and hydrocarbon-resistant.
- Midsole:** Low-density, comfortable and shockproof.

MODEL DESCRIPTION

Waterproof and breathable footwear thanks to the special HDRY membrane laminated directly to the upper in greased nubuk water-repellent. Breathable mesh fabric lining with microfiber heel abrasion resistant. Antistatic footwear with non-slip and anti-shock sole.

RECOMMENDED USES

Industry, building, handicraft, logistics.

USE AND MAINTENANCE

Make sure the shoes are in good condition before each use. Take care to regularly clean them. Do not use aggressive products such as petrol, acids and solvents that could affect their quality, safety and durability.