

RECOMMENDED USES



Wear-resistant microfibre reinforcement

Air Mesh - High-breathable and resistant inner lining

Sturdy metal eyelets

Sturdy nubuck leather uppers with mesh inserts for S1P versions

Triple seams for added strength

AP Zero - Lightweight, ultra-flexible, anti-perforation insole board

Double-density PU sole with maximum abrasion resistance and softer midsole for added comfort

ALcap - Lightweight, impact-resistant aluminium toe cap



Deep self-cleaning grooves

Punto Flex - Special technical solution that allows the foot to bend correctly

Non-slip grooves for ladders

Stabilizer - Stabilizer arch inside the sole for correct foot movement

HSA - Maximum heel shock-absorption

JUMP 750

L57012 OTD

STANDARD	SIZE
S3 SRC	38/47
COLOURS	WEIGHT
Night Olive	696 gr
Orange	
ELECTRIC CATEGORY	FIT
Antistatic	10,5

COMPONENTS:

- Upper:** Water-resistant nubuck.
- Upper lining:** Breathable mesh fabric.
- Toecap:**
 - Aluminium toe-cap.
 - Impact protection 200 Joules.
 - Compression protection 1,500 kg.

Anti-intrusion insole: Made of anti-perforation, absorbent, abrasion- and flaking-resistant fabric.

Sole: Made of dual-density antistatic PU directly injected onto the upper. With stabilizer for foot stability.

Tread: High density, non-slip (SRC), abrasion- and hydrocarbon-resistant.

Midsole: Low-density, comfortable and shockproof.

MODEL DESCRIPTION:

Low-ankle shoe with anti-puncture fabric, water-resistant nubuck upper and protective TPU toe-cap. Breathable mesh lining. Antistatic shoe with non-slip and anti-shock sole.

RECOMMENDED USES:

Industry in general, engineering, construction, warehouses, agriculture.

USE AND MAINTENANCE:

Make sure the shoes are in good condition before each use. Take care to regularly clean them. Do not use aggressive products such as petrol, acids and solvents that could affect their quality, safety and durability.