

JUMF	750
L57012	50K

STANDARD	SIZE	Тоесар:	 Aluminium toe-cap. Impact protection 200 Joules. 	Antistatic
S3 SRC	38/47	Anti-intrusion insole:	 Compression protection 1,500 kg. Made of anti-perforation, absorbent, abrasion- and flakingresistant fabric. 	RECOMMENT
COLOURS Aviator	636 gr	Sole:	Made of dual-density antistatic PU directly injected onto the upper. With stabilizer for foot stability.	USE AND MAI
Yellow		Tread:	High density, non-slip (SRC), abrasion- and hydrocarbonresistant.	Make sure Take care t
ELECTRIC CATEGORY Antistatic	FIT 10,5	Midsole:	Low-density, comfortable and shockproof.	Do not use that could

Upper:

Upper lining:

COMPONENTS:

Water-resistant nubuck.

Breathable mesh fabric.





Punto Flex -Special technical solution that allows the foot to bend correctly



Stabilizer - Stabilizer arch inside the sole for correct foot movement

MODEL DESCRIPTION:

Low-ankle shoe with anti-puncture fabric, water-resistant nubuck upper and protective TPU toe-cap. Breathable mesh lining. c shoe with non-slip and anti-shock sole.

NDED USES:

in general, engineering, construction, warehouses, agriculture.

AINTENANCE:

re the shoes are in good condition before each use. re to regularly clean them. Ise aggressive products such as petrol, acids and solvents Id affect their quality, safety and durability.