



Air Mesh - High-breathable and resistant inner lining

Wear-resistant microfi bre reinforcement

Sturdy metal eyelets



Double Laces - -Double laces for quick replacements and a touch of style

Sturdy nubuck leather uppers with mesh inserts for S1P versions



AP Zero - Lightweight, ultra-fl exible, antiperforation insole board

Double-density PU sole with maximum abrasion resistance and softer midsole for added comfort

Triple seams for added strength



ALcap - Lightweight, impact-resistant aluminium toe cap

RECOMMENDED USE



Deep self-cleaning grooves

Non-slip grooves for ladders



HSA - Maximum heel shock-absorption

Punto Flex - Special technical solution that allows the foot to bend correctly



Stabilizer - Stabilizer arch inside the sole for correct foot movement



JUMP 900 MID

L45419 OTD

STANDARD	SIZE
S3 SRC	38/47
COLORS	WEIGHT
Night Olive	635 gr
Orange	
ELECTRIC CATEGORY	FIT
Antistatic	10,5

COMPONENTS:

- Upper:** Water-resistant nubuck.
- Upper lining:** Breathable mesh fabric.
- Toe-cap:**
 - Aluminium toe-cap.
 - Impact protection 200 Joules.
 - Compression protection 1,500 kg.

Anti-puncture insole: Made of anti-perforation, absorbent, abrasion- and flakingresistant fabric.

Sole: Made of dual-density antistatic PU directly injected onto the upper. With stabilizer for foot stability.

Tread: High density, non-slip (SRC), abrasion- and hydrocarbonresistant.

Midsole: Low-density, comfortable and shockproof.

MODEL DESCRIPTION:

Low-ankle shoe with anti-perforation fabric. Upper in water-resistant nubuck. Breathable mesh lining. Antistatic shoe with non-slip and anti-shock sole.

RECOMMENDED USES:

Industry in general, engineering, construction, warehouses, agriculture.

USE AND MAINTENANCE:

Make sure the shoes are in good condition before each use. Take care to regularly clean them. Do not use aggressive products such as petrol, acids and solvents that could affect their quality, safety and durability.