



Air Mesh - High-breathable and resistant inner lining

Wear-resistance microfibre reinforcement

Sturdy metal eyelets

Sturdy nubuck leather uppers with mesh inserts for S1P versions

Triple seams for added strength



AP Zero - Lightweight, ultra-flexible, antiperforation insole board

Double-density PU sole with maximum abrasion resistance and softer midsole for added comfort



ALcap - Lightweight, impact-resistant aluminium toe cap

RECOMMENDED USE



Industry



Logistics



Handicraft



Building



Agriculture



Deep self-cleaning grooves

Non-slip grooves for ladders



HSA - Maximum heel shock-absorption

Punto Flex - Special technical solution that allows the foot to bend correctly



Stabilizer - Stabilizer arch inside the sole for correct foot movement



JUMP 925

L55266 2AF

| STANDARD | SIZE |
|-------------------|--------|
| S3 SRC | 38/47 |
| COLORI | WEIGHT |
| Black | 635 gr |
| ELECTRIC CATEGORY | FIT |
| Antistatica | 10,5 |

COMPONENTS:

- Upper:** Water-resistant nubuck and protective TPU toe-cap.
- Upper lining:** Breathable mesh fabric.
- Toe-cap:**
 - Aluminium toe-cap.
 - Impact protection 200 Joules.
 - Compression protection 1,500 kg.

Anti-puncture insole: Made of anti-perforation, absorbent, abrasion- and flaking-resistant fabric.

Sole: Made of dual-density antistatic PU directly injected onto the upper. With stabilizer for foot stability.

Tread: High density, non-slip (SRC), abrasion- and hydrocarbon-resistant.

Midsole: Low-density, comfortable and shockproof.

Low-ankle shoe with anti-puncture fabric, water-resistant nubuck upper and protective TPU toe-cap. Breathable mesh lining. Antistatic shoe with non-slip and anti-shock sole.

Industry in general, engineering, construction, warehouses, agriculture.

Make sure the shoes are in good condition before each use. Take care to regularly clean them. Do not use aggressive products such as petrol, acids and solvents that could affect their quality, safety and durability.