



Air Mesh - High-breathable and resistant inner lining

Wear-resistant microfibre reinforcement

Sturdy metal eyelets

Triple seams for added strength

Sturdy nubuck leather uppers with mesh inserts for S1P versions



AP Zero - Lightweight, ultra-flexible, anti-perforation insole board

Double-density PU sole with maximum abrasion resistance and softer midsole for added comfort



ALcap - Lightweight, impact-resistant aluminium toe cap

RECOMMENDED USES



Deep self-cleaning grooves

Punto Flex - Special technical solution that allows the foot to bend correctly

Non-slip grooves for ladders



Stabilizer - Stabilizer arch inside the sole for correct foot movement



HSA - Maximum heel shock-absorption

JUMP 950 HIGH

L49679 1F7

STANDARD	SIZE
S3 SRC	38/47
COLORS	WEIGHT
Tan Sand	625 gr
ELECTRIC CATEGORY	FIT
Antistatica	10,5

COMPONENTS:

- Upper:** Water-resistant nubuck.
- Upper lining:** Cambrelle®.
- Toe-cap:**
 - Aluminium toe-cap.
 - Impact protection 200 Joules.
 - Compression protection 1,500 kg.
- Anti-puncture insole:** Made of anti-perforation, absorbent, abrasion- and flaking-resistant fabric.
- Sole:** Made of dual-density antistatic PU directly injected onto the upper. With stabilizer for foot stability.
- Tread:** High density, non-slip (SRC), abrasion- and hydrocarbon-resistant.
- Midsole:** Low-density, comfortable and shockproof.

MODEL DESCRIPTION:

High shoe with anti-perforation fabric. Water-resistant nubuck upper. Cambrelle® lining. Antistatic shoe with non-slip and anti-shock sole.

RECOMMENDED USES:

Industry in general, engineering, construction, warehouses, agriculture.

USE AND MAINTENANCE:

Make sure the shoes are in good condition before each use. Take care to regularly clean them. Do not use aggressive products such as petrol, acids and solvents that could affect their quality, safety and durability.