



Air Mesh - High-breathable and resistant inner lining



Metalfree - Completely free of metal parts for maximum comfort and great freedom of movement

RECOMMENDED USES



Upper with quality materials for greater wear resistance

Non-slip grooves for ladders



Punto Flex - Special technical solution that allows the foot to bend correctly



ESD - Electrostatic Discharge
Electrical resistance to contain static energy and protect you from the risk of shocks



AP Zero - Lightweight, ultra-flexible, antiperforation insole board



HSA - Maximum heel shock-absorption



FLYcap - Toecap of composite material that is compression-resistant up to 200J

Double-density PU sole with maximum abrasion resistance and softer midsole for added comfort

RACE 400 MID ESD

L59843 2AZ

STANDARD	SIZE
S3 SRC	38/48
COLOURS	WEIGHT
Asphalt	580 gr
Black	
ELECTRIC CATEGORY	FIT
ESD	10,5

COMPONENTS:

- Upper:** Nubuck Crazy Horse leather with water-repellent treatment.
- Upper lining:** Breathable mesh fabric.
- Toe-cap:**
 - Multilayer composite metal-free toecap.
 - 200 joule impact protection.
 - Compression protection 1,500 kg.

Anti-intrusion insole: Made of anti-perforation, absorbent, abrasion- and flaking-resistant fabric.

Sole: Made of antistatic bidensity polyurethane, directly injected onto the upper with electrostatic charge dissipation capacity.

Tread: High density, non-slip (SRC), abrasion- and hydrocarbon-resistant.

Midsole: Low-density, comfortable and shockproof.

MODEL DESCRIPTION:

Mid shoe with anti-perforation fabric. Nubuck Crazy Horse leather upper with water-repellent treatment. Breathable mesh lining. Antistatic shoe with non-slip and anti-shock sole.

RECOMMENDED USES:

Industry, logistics, handicraft, building, agriculture.

USE AND MAINTENANCE:

Make sure the shoes are in good condition before each use. Take care to regularly clean them. Do not use aggressive products such as petrol, acids and solvents that could affect their quality, safety and durability.