



**Air Mesh** - High-breathable and resistant inner lining



**Metalfree** - Completely free of metal parts for maximum comfort and great freedom of movement

**RECOMMENDED USES**



Upper with quality materials for greater wear resistance

Non-slip grooves for ladders

**Punto Flex** - Special technical solution that allows the foot to bend correctly

Double-density PU sole with maximum abrasion resistance and softer midsole for added comfort



**FLYcap** - Toecap of composite material that is compression-resistant up to 200J



**HSA** - Maximum heel shock-absorption



**AP Zero** - Lightweight, ultra-flexible, antiperforation insole board



# RACE 200

## L59832 OXH

| STANDARD          | SIZE   |
|-------------------|--------|
| S3 SRC            | 36/48  |
| COLOURS           | WEIGHT |
| Asphalt           | 570 gr |
| Green Acacia      |        |
| ELECTRIC CATEGORY | FIT    |
| Antistatic        | 10,5   |

**Upper:** Water-resistant Action Nubuck leather.  
**Upper lining:** Breathable mesh fabric.  
**Toe-cap:**

- Multilayer composite metal-free toecap.
- 200 joule impact protection.
- Compression protection 1,500 kg.

**Anti-intrusion insole:**

Made of anti-perforation, absorbent, abrasion- and flaking-resistant fabric.

**Sole:**

Made of antistatic bidensity polyurethane, directly injected onto the upper with electrostatic charge dissipation capacity.

**Tread:**

High density, non-slip (SRC), abrasion- and hydrocarbon-resistant.

**Midsole:**

Low-density, comfortable and shockproof.

**COMPONENTS:**

**MODEL DESCRIPTION:**

Low-ankle shoe with anti-perforation fabric. Upper in water-resistant nubuck. Breathable mesh lining. Antistatic shoe with non-slip and anti-shock sole.

**RECOMMENDED USES:**

Industry, logistics, handicraft, building, agriculture.

**USE AND MAINTENANCE:**

Make sure the shoes are in good condition before each use. Take care to regularly clean them. Do not use aggressive products such as petrol, acids and solvents that could affect their quality, safety and durability.