



Air Mesh - High-breathable and resistant inner lining



Metalfree - Completely free of metal parts for maximum comfort and great freedom of movement

RECOMMENDED USES



Upper with quality materials for greater wear resistance

Non-slip grooves for ladders

Punto Flex - Special technical solution that allows the foot to bend correctly



AP Zero - Lightweight, ultra-flexible, antiperforation insole board



HSA - Maximum heel shock-absorption

Double-density PU sole with maximum abrasion resistance and softer midsole for added comfort



FLYcap - Toecap of composite material that is compression-resistant up to 200J

RACE 900 MID

L59840 2AZ

STANDARD	SIZE
S3 SRC	38/48
COLOURS	WEIGHT
● Black	585 gr
● Asphalt	
ELECTRIC CATEGORY	FIT
Antistatic	10,5

COMPONENTS:

- Upper:** Water-resistant patent leather.
- Upper lining:** Breathable mesh fabric.
- Toe-cap:**
 - Multilayer composite metal-free toecap.
 - 200 joule impact protection.
 - Compression protection 1,500 kg.

Anti-intrusion insole: Made of anti-perforation, absorbent, abrasion- and flaking-resistant fabric.

Sole: Made of antistatic bidensity polyurethane, directly injected onto the upper with electrostatic charge dissipation capacity.

Tread: High density, non-slip (SRC), abrasion- and hydrocarbon-resistant.

Midsole: Low-density, comfortable and shockproof.

MODEL DESCRIPTION:

Mid shoe with anti-perforation fabric. Water-resistant leather upper. Breathable mesh lining. Antistatic shoe with non-slip and anti-shock sole.

RECOMMENDED USES:

Industry, logistics, handicraft, building, agriculture.

USE AND MAINTENANCE:

Make sure the shoes are in good condition before each use. Take care to regularly clean them. Do not use aggressive products such as petrol, acids and solvents that could affect their quality, safety and durability.