



**Air Mesh** - High-breathable and resistant inner lining



**Metalfree** - Completely free of metal parts for maximum comfort and great freedom of movement

Upper with quality materials for greater wear resistance



Non-slip grooves for ladders

**Punto Flex** - Special technical solution that allows the foot to bend correctly



**HSA** - Maximum heel shock-absorption



**AP Zero** - Lightweight, ultra-flexible, antiperforation insole board

Double-density PU sole with maximum abrasion resistance and softer midsole for added comfort



**FLYcap** - Toecap of composite material that is compression-resistant up to 200J

# RACE 901

## L59841 2AZ

STANDARD	SIZE
S1 SRC	36/48
COLOURS	WEIGHT
● Black	500 gr
● Asphalt	
ELECTRIC CATEGORY	FIT
Antistatic	10,5

### COMPONENTS:

- Upper:** Pigmented, patent leather.
- Upper lining:** Breathable mesh fabric.
- Toe-cap:**
  - Multilayer composite metal-free toecap.
  - 200 joule impact protection.
  - Compression protection 1,500 kg.
- Sole:** Made of antistatic bidensity polyurethane, directly injected onto the upper with electrostatic charge dissipation capacity.
- Tread:** High density, non-slip (SRC), abrasion- and hydrocarbon-resistant.
- Midsole:** Low-density, comfortable and shockproof.

### MODEL DESCRIPTION:

Low-ankle shoe with pigmented and breathable leather upper. Breathable mesh lining. Antistatic shoe with non-slip and anti-shock sole.

### RECOMMENDED USES:

Industry, logistics, handicraft, building, agriculture.

### USE AND MAINTENANCE:

Make sure the shoes are in good condition before each use. Take care to regularly clean them. Do not use aggressive products such as petrol, acids and solvents that could affect their quality, safety and durability.