

HCT - Soft EVA sole + heat-resistant SRC non-slip rubber outsole

Metalfree - Completely free of metal parts for maximum comfort and great freedom of movement

Washable and antibacterial anatomical open-cell PU footbed

FLYcap - Toecap of composite material that is compression-

resistant up to 200J

AP Zero next - Next-generation lightweight, ultra-flexible anti-perforation insole boards

RECOMMENDED USES



Industry









Outsole with selfcleaning grooves for use in all conditions

Non-slip grooves for ladders



Stabilizer - Stabilizer arch inside the sole for correct foot movement

Punto Flex - Special technical solution that allows the foot to bend correctly



HSA - Maximum heel shock-absorption

SKATE L58095 50R

Antistatic

35/47 COLOURS WEIGHT 510 gr Chalk ELECTRIC CATEGORY FIT 10,5

Upper lining: Toe-cap:

Anti-puncture insole:

Scratch-resistant, tear-resistant suede crust leather.

Breathable mesh fabric.

- · Aluminium toe-cap.
- Impact protection 200 Joules.
- Compression protection 1,500 kg.

Made of anti-perforation, absorbent, abrasion- and flakingresistant fabric.

COMPONENTS:

Made of antistatic rubber + soft EVA, glued to the upper. With

stabilizer for foot stability. Tread:

antistatic rubber, non-slip (SRC), abrasion- and hydrocarbonresistant.

Midsole:

EVA, soft, comfortable and anti-shock.

MODEL DESCRIPTION:

Low-ankle shoe with anti-perforation fabric. Crust Suede leather upper which is scratch- and tear-resistant.

Antistatic shoe with non-slip and anti-shock sole.

RECOMMENDED USES:

Breathable mesh lining.

Industry, handicraft, logistics.

USE AND MAINTENANCE:

Make sure the shoes are in good condition before each use. Take care to regularly clean them.

Do not use aggressive products such as petrol, acids and solvents that could affect their quality, safety and durability.