



Air Mesh - High-breathable and resistant inner lining



Metalfree - Completely free of metal parts for maximum comfort and great freedom of movement



Double Laces - Double laces for quick replacements and a touch of style



FLYcap - Toecap of composite material that is compression resistant up to 200J

TPU heel protector

Ortholite® - washable antibacterial footbed



HCT - Innovative sole giving maximum cushioning and excellent walk-energy return



AP Zero - Lightweight, ultra-flexible, antiperforation insole board

Upper in sturdy suede leather with technical-material inserts for utmost resistance

RECOMMENDED USES



Industry



Handicraft



Logistics



HRO - Soft EVA sole + heatresistant SRC non-slip rubber outsole

Outsole for maximum indoor stability



HSA - Maximum heel shock-absorption

Punto Flex - Special technical solution that allows the foot to bend correctly

STREET
L49685 1MY

STANDARD	SIZE
S1P SRC HRO	38/47
COLOURS	WEIGHT
● Black	560 gr
● Grey Cement	
ELECTRIC CATEGORY	FIT
Antistatic	9,5

COMPONENTS:

- Upper:** Scratch-resistant suede crust leather.
- Upper lining:** Breathable mesh fabric.
- Toe-cap:**
 - Aluminium toe-cap.
 - Impact protection 200 Joules.
 - Compression protection 1,500 kg.

Anti-puncture insole: Made of anti-perforation, absorbent, abrasion- and flakingresistant fabric.

Sole: Antistatic rubber + soft EVA, upper glued to the upper.

Tread: antistatic rubber, non-slip (SRC), abrasion and hydrocarbon resistant. HRO heat resistant by contact.

Midsole: EVA, soft, comfortable and anti-shock.

MODEL DESCRIPTION:

Low-ankle shoe with anti-perforation fabric. Scratch-resistant crust suede upper. Breathable mesh lining. Antistatic shoe with non-slip and anti-shock sole.

RECOMMENDED USES:

Industry, handicraft, logistics

USE AND MAINTENANCE:

Make sure the shoes are in good condition before each use. Take care to regularly clean them. Do not use aggressive products such as petrol, acids and solvents that could affect their quality, safety and durability.